



## 130-bbl Vacuum Transports

PCI Manufacturing Solutions' 130-bbl standard vacuum trailers are a solid offering in the company's product line. Standard features include three-point suspension, two-speed crank landing legs and ¼" ASTM A36, sub-arced steel barrel; each barrel is fully gusseted and padded to withstand the rigors of both on and off road.



No need to worry about stepping over hoses or through mud—PCI's vacuum trailer allows easy access from the ground to the upper walkway. The long wedge sump offers room for 4" and 6" loading lines, giving you all the flexibility

### Standard Vacuum Trailer Specifications:

- ✓ 130-bbl capacity
- ✓ Barrels are sub-arc welded and tested to 20 psi design pressure
- ✓ Two internal baffles made of flat plate and strapped to ensure full coating coverage
- ✓ External 2.5" strap supports
- ✓ ASTM A36 steel, ¼" heads and shell
- ✓ Ultra-heavy-duty rear bumper
- ✓ Adjustable kingpin plate
- ✓ Two-speed, crank landing legs
- ✓ Full length hose troughs with drains
- ✓ Walkways/handrails: side and rear entry to catwalk
- ✓ 2" sight-glass fittings, front driver and rear passenger side
- ✓ DOT-approved LED lighting with custom-fit, plug-and-go wiring harness
- ✓ Dual tool boxes with heavy duty lids and door chains mounted within a steel cradle
- ✓ 15 psi pressure/vacuum vents
- ✓ Three 20" top manways
- ✓ 12" primary scrubber
- ✓ 10-gal. secondary scrubber
- ✓ Three-point, eight-leaf suspension
- ✓ 11R-24.5" chip-resistant radial tires
- ✓ 22,500-lb axle with auto slack adjusters
- ✓ Carboline Phenoline® 310 two-part epoxy coating
- ✓ Primer plus one-color Strathmore DTM paint



### Options:

PCI Manufacturing Solutions offers the following options, allowing customers to create a custom trailer, built to satisfy their specific needs.

- Gel/belly lines or belly nipples
- Optional pre-fabricated hose-trough mount for trailer-mounted pumps
- Hose-trough-mounted vacuum pumps (complete modified tray with catch muffler and ready-to-install pump)
- Spray-in liner for hose troughs
- 8" float ball
- Hoses cut to length
- 4" front cleanout plugs
- 1.5" blow-down valve at rear fill lines
- Pump/engine kits (self-contained)
- Air-ride suspension (25,000-lb axle)
- Single-point suspension (25,000-lb axle)
- Drip tray under butterfly valves
- Water-transport only versions
- 130 and 165 bbl capacities available