



## 250-bbl Mini-Frac

The Mini-Frac tank provides the high quality PCI Manufacturing Solutions' customers have come to expect, while creating a smaller site footprint. Ideal for smaller sites typical of refineries, industrial and manufacturing customers where space is in short supply, this tank makes every inch count. Made to perform, the PCI Mini-Frac endures the stresses of the oil and gas industry.

### Standard Tank Specifications:

- ✓ 250-bbl capacity
- ✓ ¼" corrugated steel walls
- ✓ Top panels with stiffening ribs and 2 non-sealable hatches with hinged lids
- ✓ V-bottom or flat floor
- ✓ One 3" fill line
- ✓ Two 22" manways, front and passenger side rear.
- ✓ 4" butterfly valve, front and rear
- ✓ Front- and rear-mounted ladders for top access
- ✓ Carboline Phenoline® 310 interior liner (two-part epoxy)
- ✓ High-solids, high-gloss Strathmore DTM exterior paint. Customer color choice to minimum 6-mil dry film thickness

---

### Options:

PCI Manufacturing Solutions offers the options listed below, allowing customers to create a custom tank, built to satisfy their specific needs.

- Weir wall
- 4" recessed suction lines
- Tank lifting eyes
- Diffusers
- Open top
- Roll off or skidded
- Roof-mounted safety cable

