



440-bbl Double-Wall, Round-Bottom Tanks

PCI Manufacturing Solutions' double-wall, round-bottom tanks are built for single-unit secondary containment. With double walls on five sides, this tank allows you to breathe easy knowing that any breach of the inner tank would be automatically contained for easy cleanup.

Double-Wall Tank Specifications:

- ✓ 440-bbl capacity
- ✓ Corrosion-resistant design
- ✓ Custom-fit, plug-and-go wiring harness
- ✓ ASTM A36 ¼" smooth inner walls, with ¼" corrugated steel outer walls
- ✓ Top panels with stiffening ribs and two sealed hatches with hinged lids and anti-personnel bars
- ✓ 3" 150# blind-flanged coupling on the top
- ✓ 8" roof-mounted pressure/relief valve
- ✓ 4" 150# blind flange on the top
- ✓ 1" threaded nipple with interstitial mushroom vent on the top
- ✓ Front stair and walkway assembly to top of tank
- ✓ 4" front drain with butterfly valve
- ✓ 4" front wall penetration with butterfly valve
- ✓ 4" rear drain with butterfly valve and remote handle
- ✓ One 2" rear interstitial drain
- ✓ 11R-22.5" radial tires
- ✓ 25,000-lb axle
- ✓ 100% solids, high-performance Carboline Phenoline® 310 interior liner, minimum 15-mil dry film thickness
- ✓ High-solids, high-gloss Strathmore DTM exterior paint, 6-mil dry film thickness, customer color choice



Options:

PCI Manufacturing Solutions offers the options listed below, allowing customers to create a custom tank, built to satisfy their specific needs.



Sign Plates

- 36" x 60" mid-tank, 2 per tank
- Custom size: _____

Decals

- Customer logo

Rear Fill Line

- 3"
- 4"
- 6"

Other

- Internal ladders with foldable outer grab rails on top
- Float ball assembly
- Roof-mounted safety cable