



Watertight Rolloff Containers

Designed for transport by roll-off trucks, these containers are commonly used to transport industrial and paint waste or other waste types, like construction or demolition, that require removing large quantities of material. The material in the roll-off may be taken to a landfill, recycled or disposed of/recovered in



some other way. Dewatering Boxes are roll-off containers with a steel screen covering the interior of the box, leaving the gate end open for easy dumping. These are perfect for freeing water from things like sludge or slurry from a work site.

Standard Specifications for all Watertight Rolloff Containers:

Walls: ASTM A36 7-gauge formed side with radius bottom

Floor: ASTM A36 ¼" bottom plate with C3

× 4.1# cross supports

Bulkhead: ASTM A36 7-gauge plate with A-frame formed channel

Rear Door: ASTM A36 7-gauge plate with formed channel stiffeners, T-style gasket for water-tight seal and two steel hinges with grease fittings

Rear Door Securement: Side-operated latch with 4 (four) ratchet binders (2 on center at each side of door, 2 at bottom of door with chain guards)

Lifting System: 1" A36 recessed tow hook

Undercarriage: 6 × 2 × ¼" tubing for main rails, 4 × 6" steel with greaseable axle for nose rollers and 8 × 10" steel with greaseable axle for ground rollers

Tarp Assembly: 18-oz vinyl with reinforced corners, pockets and strap cutouts with five ¾" tarp bows; roll pipe made of 1½" galvanized tubing

Internal Coating: Epoxy primer only

External Paint: One-color, direct-to-metal paint



25-Yard Watertight Rolloff with Dewatering Box

All Standard specifications plus:

Capacity: 20 yards with the dewatering box in place

Overall Height: 5'3"

Overall Width: 8'6"

Overall Length: 23'1"

Box Height: 4'5"

Box Width: 7'4"

Box Length: 21'8"

Weight: 6,400 lbs. With basket: 8,460 lbs.

Drains: Two 3" threaded, capped drains at floor level – one at front left and one at the right rear

Basket: Expanded metal floor plus expanded metal sides with ~6" of clearance around basket. Outer frame constructed of 4" C-channel runners and 2"×2" tubing cross supports with 9-gauge expanded metal floor and walls. Basket bolted to the upper frame of the roll-off for easy removal and cleaning. Interior J-hooks around the upper perimeter of the basket secure the filter cloth.

Basket Weight: 2,060 lbs.

20- & 25-YD Watertight Rolloffs with Canvas Roll Tarp		
Capacity	20-Yard	25-Yard
Overall Height	4'5"	5'3"
Overall Width	8'6"	8'6"
Overall Length	23'1"	23'1"
Box Height	3'7"	4'5"
Box Width	7'4"	7'4"
Box Length	21'8"	21'8"
Weight (in lbs.)	5840	6400

